

TTR HD/SD Portable 4 Output Re-Clocking DA

HD/SD SDI Portable DA

TTR



This amplifier has been primarily designed for field operational use.

TTR have designed this Serial Digital HDTV DA to be small, low-cost and low on power consumption. It provides four HDTV outputs as well as a looping input. It can be used to drive HDTV signals up to 110m when using high quality HDTV video cable. Power can be supplied from an external 12Volt DC supply or via a battery mounted on the optional onboard PAG™ Or Anton Bauer™ mounted battery clip.

Features

- Low power consumption typically 200mA
- Up to 30 hours battery life
- Re-clocked outputs to substantially reduce input jitter
- Looping Input
- Automatic input equalisation
- UL approved 110/240Vac power supply included
- Suitable for 270Mb/s, 360Mb/s and HDTV rates
- Power and signal presence LED indicators
- Rack mount kit available

Specifications

VIDEO	<ul style="list-style-type: none">● Input impedance 75 Ohm● Nominal Input Level 800mv
INPUTS	<ul style="list-style-type: none">● 1 x BNC Input● 1 x BNC for lower loop through inputs
OUTPUTS	<ul style="list-style-type: none">● 4 x BNC
POWER	<ul style="list-style-type: none">● 12V DC
CASE	<ul style="list-style-type: none">● Package Height Width Depth Weight
CONNECTOR TYPES	<ul style="list-style-type: none">● Video BNC

NORTH AMERICAN DISTRIBUTOR
BlueScreen LLC
137 N. Larchmont, Suite 508
Los Angeles, CA 90004
Telephone 323-467-7572
Principals: Gayle Comstock, Bob Kertesz
Email: bob@bluescreen.com

TTR

TTR Ltd
84 Bridge Road,
Chertsey, Surrey
KT16 8LA. England.
Telephone: +44 (0) 1932 561063
Fax: +44 (0) 1932 885182
E-mail: Sales@ttr.co.uk

HD/SD 4 Output DA